LAND
ULTIMATE HEAD PROTECTION

SPECIFICATION SHEET

TYPE II · CLASS C & E SAFETY HELMET

FRONTIER

Low-profile helmet with 360° impact protection, in vented Class C and non-vented Class E models.



Type II
Top + side impact

Class C & E
E tested to 20,000 V

550 / 620 g
Weight, Class C / E

52–63 cm
Head size range

Vented
Class C models

CERTIFICATIONS

ANSI/ISEA Z89.1	Type II (2014 ed.), certified by COLTS & SEI
Class E / Class G	Tested to 20,000 V / 2,200 V
Class C	Vented; no electrical protection
EN 397	Tested from -30 °C to +50 °C

MATERIALS

Shell	PC-ABS, high-performance
Impact liner	Full-coverage EPS
Comfort pads	Microfiber crown pad, washable sweatband

KEY FEATURES

360° impact protection — full-coverage EPS liner guards against hits from multiple directions

Vented design — airflow on long shifts (Class C)

Quick-dial ratchet — adjusts with gloves on

4-point chin strap — magnetic quick-release buckle

Accessory ready — headlamp clip slots; fits common face shields and hearing protection

CARE

1. Inspect shell, EPS liner, suspension, ratchet, chin strap and accessories before each use.
2. Clean with mild soap and lukewarm water. No harsh chemicals, solvents or abrasives.
3. Machine-wash the removable sweatband. Let everything dry fully.
4. Store in a clean, dry, protected place.

BUILT FOR Construction • Rescue & rope access • HVAC • Utility maintenance • Industrial work

ORDER

Class C Vented	● **Blue** · LAND-02C-BL	● **Carbon Fiber** · LAND-02C-CF
	○ **White** · FRONTR-V-WT-NA-US	● **Lime Green** · FRONTR-V-LG-NA-US
Class E Non-vented	○ **White** · LAND-02E-WT	● **Blue** · LAND-02E-BL

(714) 886-2013 info@landhelmets.com **landhelmets.com**