

TYPE II CLASS C & E SAFETY HELMET

PRODUCT FEATURES:

- **360° Impact Protection:** Designed for Type II protection with a full-coverage EPS liner and secure 4-point chin strap to help protect against impacts from multiple directions.
- **Low-Profile, Heavy-Duty Shell:** The durable PC-ABS shell combines strong impact resistance with a streamlined, lightweight design, making it suitable for demanding work environments and a wide range of temperatures.
- **Vented Design:** Strategically positioned ventilation openings improve airflow and help reduce heat buildup during long work shifts.
- **Quick-Dial Ratcheting Suspension:** Easy-to-adjust ratchet system provides a secure, comfortable fit and can be operated while wearing gloves. Fits head sizes approximately 52–63 cm.
- **Magnetic Chin Strap Buckle:** The 4-point magnetic buckle allows for fast, convenient fastening and release, helping crews put on and remove the helmet quickly and easily.
- **Accessory Ready:** Designed with integrated headlamp clip slots and compatibility with commonly used face shields and hearing protection. Available in high-visibility color options for improved jobsite visibility

TECHNICAL DATA:

HELMET

- **Material**
 - PC-ABS Shell (Polycarbonate/Acrylonitrile Butadiene Styrene): High-performance outer shell offering a blend of durability and lightness.
- **Weight:** 550g (C) / 620g(E)
- **Size:** 52 cm - 63 cm
- **Vented:** Yes (Class C), No (Class E)

INTERIOR

- **EPS (Expanded Polystyrene) Liner:** Energy-absorbing liner to provide comprehensive impact protection.
- **Microfiber Crown Pad & Washable Sweatband:** Enhanced comfort and hygiene, ideal for long work shifts.



STANDARDS & COMPLIANCE:

- ANSI/ISEA Z89.1-2014 Type II certified by COLTS & SEI
- Class C (Conductive) – No electrical protection.
- Class E (Electrical): Tested up to 20,000 volts.
- Class G (General): Tested up to 2,200 volts.
- EN 397 – Tested from -30°C to +50°C for performance across extreme conditions.

APPLICATIONS & CARE:

Applications: Construction, Rescue & Rope Access, HVAC, Utility Maintenance, Industrial Work Environments

Care: Inspect the shell, EPS liner, suspension, ratchet, chin strap, and accessories before use. Clean with mild soap and lukewarm water; avoid harsh chemicals, solvents, and abrasive cleaners. The removable sweatband is machine-washable. Allow all components to dry completely and store the helmet in a clean, dry, protected location.

ORDERING INFORMATION:

Class C:

Blue (LAND-02C-BL)
Carbon Fiber (LAND-02C-CF)
White (FRONTR-V-WT-NA-US)
Lime Green (FRONTR-V-LG-NA-US)

Class E:

White (LAND-02E-WT)
Blue (LAND-02E-BL)